


HT-550A Tracked remote-controlled lawn mower



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-550A			
Cutting width	550mm	Start mode	Hand pulled/One key start
Height adjustment method	Remote operation	Charge mode	Engine self charging system
Stubble height	20-150mm	Operating mode	Remote operation
Walking speed	0-3km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-1650 m ² /h
Product size	920mm*930mm*580mm	Net weight	137kg
Package size	970mm*980mm*730mm	Package weight	168kg
Engine	LONCIN196CC/LONCIN224CC/YAMAHA190CC/KOHLER200CC/RATO200CC		



Cage structure
Strengthen the rigidity of the entire machine



Remote control lifting and lowering of the cutterhead height



Lawn mower special track



Dual LED headlights



HT-520 Tracked remote-controlled lawn mower



Double layered support wheel design ensures more stable machine operation.

Using 16 sets of high-strength manganese steel blades, it is durable and long-lasting.

The front anti flying metal curtain prevents stones and blades from splashing, making mowing safer.



MODEL: HT-520			
Cutting width	520mm	Start mode	Hand pull/Electric start
Height adjustment method	Manual	Charging mode	Engine self charging system
Stubble height	30-120mm	Operation mode	Remote control operation
Walking speed	0-4.7km/h	Remote control distance	0-680m
Working slope	0-30°	Mowing efficiency	0-2400 m ² /h
Product size	1050mm*970mm*620mm	Net weight	198kg
Packaging size	1100mm*1020mm*700mm	Packaging weight	220kg
Engine	ZONSEN 225cc gasoline engine/KOOP 178F diesel engine		

HT-550B Tracked remote-controlled lawn mower



HT-550D Four wheel drive remote control lawn mower



-  Full of power
-  Fast weeding
-  Effective distance
-  Intelligent design
-  Remote control
-  Wide applicability
-  Excellent quality
-  Safe and secure

MODEL: HT-550B			
Cutting width	550mm	Start mode	Hand pull/One key start
Height adjustment method	Remote control/Manual	Charging mode	Engine self charging system
Stubble height	20-150mm	Operation mode	Remote control operation
Walking speed	0-3km	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-1650 m²/h
Product size	920mm*930mm*480mm	Net weight	132kg
Packaging size	970mm*980mm*620mm	Packaging weight	159kg
Engine	LONCIN196CC/LONCIN224CC/YAMAHA190CC/KOHLER200CC/RATO200CC		

-  Full of power
-  Fast weeding
-  Effective distance
-  Intelligent design
-  Remote control
-  Wide applicability
-  Excellent quality
-  Safe and secure

MODEL: HT-550D			
Cutting width	550mm	Start mode	Hand pull/One key start
Height adjustment method	Manual operation	Charging mode	External charging/Self charging
Stubble height	20-150mm	Operation mode	Remote control operation
Walking speed	0-3.5km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-1900 m²/h
Product size	1000mm*830mm*460mm	Net weight	103kg
Packaging size	1050mm*880mm*610mm	Packaging weight	135kg
Engine	LONCIN196CC/LONCIN224CC/YAMAHA190CC/KOHLER200CC/RATO200CC		

HT-550H Tracked remote-controlled lawn mower



Full of power



Fast weeding



Effective distance



Intelligent design



Remote control



Wide applicability




Excellent quality




Safe and secure

MODEL: HT-550H			
Cutting width	550mm	Start mode	Hand pull/One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	20-150mm	Operation mode	Remote control operation
Walking speed	0-4km/h	Remote control distance	0-300m
Working slope	0-45°	Mowing efficiency	0-2200 m ² /h
Product size	915mm*935mm*560mm	Net weight	175kg
Packaging size	970mm*990mm*610mm	Packaging weight	195kg
Engine	LONCIN224CC/KOHLER200		



HT-800A Tracked remote-controlled lawn mower



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-800A			
Cutting width	800mm	Start mode	One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	20-180mm	Operation mode	Remote control operation
Walking speed	0-3.5km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-2800 m ² /h
Product size	1100mm*1200mm*620mm	Net weight	233kg
Packaging size	1170mm*1250mm*760mm	Packaging weight	285kg
Gasoline tank capacity	15L	Oil tank capacity	1.2L
Engine	LONCIN452CC/LONCIN608CC/LONCIN764CC/RATO450CC/RATO740CC		




HT-800B Tracked remote-controlled lawn mower



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-800B			
Cutting width	800mm	Start mode	One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	20-180mm	Operation mode	Remote control operation
Walking speed	0-3.5km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-2800 m ² /h
Product size	1280mm*1230mm*500mm	Net weight	180kg
Packaging size	1340mm*1280mm*660mm	Packaging weight	209kg
Gasoline tank capacity	5.5L	Oil tank capacity	1.2L
Engine	LONCIN452cc		

HT-800T Tracked remote-controlled lawn mower



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-800T			
Cutting width	800mm	Start mode	One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	30-200mm	Operation mode	Remote control operation
Walking speed	0-3.5km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-2800 m ² /h
Product size	1420mm*1320mm*760mm	Net weight	287kg
Packaging size	1470mm*1320mm*900mm	Packaging weight	356kg
Gasoline tank capacity	15L	Oil tank capacity	1.2L
Engine	LOCIN608CC/LOCIN764CC/RATO740CC		

HT-800PRO Tracked remote-controlled lawn mower



Brushless motor with gearbox



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-800PRO			
Cutting width	800mm	Start mode	One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	30-200mm	Operation mode	Remote control operation
Walking speed	0-5km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-4000 m ² /h
Product size	1420mm*1320mm*760mm	Net weight	287kg
Packaging size	1470mm*1320mm*900mm	Packaging weight	356kg
Gasoline tank capacity	15L	Oil tank capacity	1.2L
Engine	LONCIN608CC		

HT-1000A Tracked remote-controlled lawn mower



-  Full of power
-  Fast weeding
-  Effective distance
-  Intelligent design
-  Remote control
-  Wide applicability
-  Excellent quality
-  Safe and secure

MODEL: HT-1000A			
Cutting width	1000mm	Start mode	One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	20-180mm	Operation mode	Remote control operation
Walking speed	0-3.5km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-3500 m ² /h
Product size	1220mm*1400mm*620mm	Net weight	248kg
Packaging size	1270mm*1450mm*760mm	Packaging weight	310kg
Gasoline tank capacity	15L	Oil tank capacity	1.2L
Engine	LONCIN452CC/LONCIN608CC/LONCIN764CC/RATO450CC/RATO740CC		


HT-1000H Tracked remote-controlled lawn mower



-  Full of power
-  Fast weeding
-  Effective distance
-  Intelligent design
-  Remote control
-  Wide applicability
-  Excellent quality
-  Safe and secure

MODEL: HT-1000H			
Cutting width	1000mm	Start mode	One key start
Height adjustment method	Remote control operation	Charging mode	Engine self charging system
Stubble height	20-150mm	Operation mode	Remote control operation
Walking speed	0-4km/h	Remote control distance	0-450m
Working slope	0-45°	Mowing efficiency	0-4000 m ² /h
Product size	1287mm*1372mm*624mm	Net weight	295kg
Packaging size	1350mm*1420mm*750mm	Packaging weight	360kg
Gasoline tank capacity	9L	Oil tank capacity	1.2L
Engine	LOCIN 608CC		

HT-550E Tracked remote-controlled lawn mower



Full of power



Fast weeding



Effective distance



Intelligent design



Remote control



Wide applicability



Excellent quality



Safe and secure

HT-1100E Tracked remote-controlled lawn mower



Full of power



Fast weeding



Effective distance



Intelligent design



Remote control



Wide applicability



Excellent quality



Safe and secure

MODEL: HT-550E			
Cutting width	550mm	Working voltage	24V
Height adjustment method	Remote control operation	Charging mode	External charging
Stubble height	20-180mm	Operation mode	Remote control operation
Walking speed	0-3km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-1650 m ² /h
Product size	970mm*930mm*610mm	Net weight	156kg
Packaging size	1030mm*980mm*770mm	Packaging weight	189kg
Endurance time	8h		

MODEL: HT-1100E			
Cutting width	1100mm	Working voltage	24V
Height adjustment method	Remote control operation	Charging mode	External charging
Stubble height	20-180mm	Operation mode	Remote control operation
Walking speed	0-3.2km/h	Remote control distance	0-680m
Working slope	0-45°	Mowing efficiency	0-3300 m ² /h
Product size	1100mm*1500mm*620mm	Net weight	215kg
Packaging size	1150mm*1550mm*750mm	Packaging weight	275kg
Endurance time	5h		

HT-80A Tracked remote-controlled lawn mower



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-80A			
Cutting width	800mm	Cutting knife form	Y-shaped vertical knife
Height adjustment method	Hand movement	Number of blades	16 sets/32 pieces
Stubble height	20-200mm	Start mode	Electric start
Walking speed	0-5km/h	Operation mode	Remote control operation
Working slope	0-45°	Charging mode	Engine self charging system
Product size	1560mm*980mm*820mm	Mowing efficiency	0-4000軋/h
Packaging size	1620mm*1040mm*1030mm	Net weight	338kg
Engine	KOOP192F 12HPY	Packaging weight	398kg

HT-100A Tracked remote-controlled lawn mower



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-100A			
Cutting width	1000mm	Cutting knife form	Y-shaped vertical knife
Height adjustment method	Hand movement	Number of blades	20sets/40pieces
Stubble height	20-200mm	Start mode	Electric start
Walking speed	0-5km/h	Operation mode	Remote control operation
Working slope	0-45°	Charging mode	Engine self charging system
Product size	1560mm*980mm*820mm	Mowing efficiency	0-5000軋/h
Packaging size	1620mm*1040mm*1030mm	Net weight	346kg
Engine	KOOP192F 12HPY	Packaging weight	415kg

HT-120A Tracked remote-controlled lawn mower





- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

MODEL: HT-120A			
Cutting width	1200mm	Cutting knife form	Y-shaped vertical knife
Height adjustment method	Hand movement	Number of blades	24sets/48pieces
Stubble height	20-200mm	Start mode	Electric start
Walking speed	0-5km/h	Operation mode	Remote control operation
Working slope	0-45°	Charging mode	Engine self charging system
Product size	1560mm*1380mm*820mm	Mowing efficiency	0-6000㎡/h
Packaging size	1620mm*1430mm*1030mm	Net weight	356kg
Engine	KOOP195 15HPY	Packaging weight	432kg



HT-80S Tracked remote-controlled lawn mower



Full of power Fast weeding Effective distance Intelligent design Remote control Wide applicability Excellent quality Safe and secure

MODEL: HT-80S

Cutting width	800mm	Working voltage	24V
Height adjustment method	Remote control operation	Throttle adjustment method	Remote control operation
Stubble height	20-200mm	Engine start stop mode	Remote control operation
Walking speed	0-3.6km/h	Clutch control mode	Remote control operation
Working slope	0-45°	Cutting knife form	✿-shaped vertical knife
Product size	1560mm*980mm*820mm	Number of blades	20sets/60 pieces
Packaging size	1620mm*1040mm*1030mm	Mowing efficiency	0-2880 载/h
Charging mode	Engine self charging system	Net weight	350kg
Operation mode	Remote control operation	Packaging weight	460kg
Engine	B&S 420CC/KOOP195F/KOOP1100F/KOOP1105F		



Fully hydraulic remote control platform---Smart tiger 40



- Full of power
- Fast weeding
- Effective distance
- Intelligent design
- Remote control
- Wide applicability
- Excellent quality
- Safe and secure

Smartiger 40			
ENGINE		HYDRAULICS	
Maker	YANMAR /CHANGHAI	Pumps	3-tandem piston pump 1 gear pump (P&G)
Type	4-cycle, Inline, Water-cooled Diesel	Driving motors	High torque motor (Poclain)
Torque	107.7 Nm	Flail head motor	High speed motor (P&G)
Fuel	Diesel	Independent flail head circuit	Closed circuit piston
Fuel tank capacity	28 litres	Independent track drive circuit	2x closed circuit piston
Combustion system	Direct Injection	Independent motions circuit	Open circuit gear
Gross output	28.2Kw (38.3Hp) @2600rpm	Oil tank capacity	23 litres (40 litres held in system)
Transmission	Fine control hydrostatic	Attachment capacity	750Kg
Water-cooled radiator	2-core heavy duty	TRACKS	
Self-cleaning(optional)	Standard manual and automatic (optional)	Rubber	Hieghtened teeth rubber track (max working angle 55°)
REMOTE CONTROL			
Working range	>150m	DIMENSIONS	
Frequency	434MHz	Overall width (with flail head)	1500mm
Battery	Interchageable, rechargeable Two with each unit charge on machine	Overall width (with flail head)	2900mm
Proportional Joysticks	Standard	Overall height (with flail head)	1300mm
PROTECTION AND SAFETY			
Emergency stop	One-touch shut-off switch	Smartiger	1250kg
Over-slope	Automatic waring (Horn+Light) and shut-off	Flail head	200kg
Headlamp	LED	PERFORMANCE	
Signal loss	Automatic shut-off	Gradient	Working on slopes up to 55° in any direction(alarm at 50° and automatic shut-off at 55°)
Others	Automatic shut-off if hydraulic oil and lube pressure anomaly	Potentiometer speed control (0 to 100%)	1st gear (low range) Forward and backward 0-4 Km/h 2nd gear (high range) Forward and backward 0-9 Km/h
		Parking	Yes
		Steering	Skid-steering (support pivot-steering)
		Travelling bias correction on slope	Yes
ATTACHMENT / FLAIL HEAD (STANDARD)			
Standard attachment	Flail head	Rotor width	1350mm
Oil flow	84L/min	Rotor diameter	300mm
Pressure	250bar	Cutting height range (via roller adjustment)	30mm-90mm (3 positions) flail can be lifted to cut higher than 90mm
Rotor speed	3000rpm	Hydraulic lift	-200mm to 500mm
Front and rear flap	Chain and rubber	Auto-float capacity	Yes (follow ground contour up-down 10°)
Flails	Y-Flails for grass cutting and light wood up to 30mm diameter		