

CNB POWER

Quality Maker

CNBPOWER® SERIES 5

525-545W Mono FULL BLACK

144 Half-Cell Layout
M10/182mm Cell



Full Black Appearance
for Aesthetic Effect



Gallium-doped Technology



Half Cut Cell Technology




Anti-PID
Low LID
Performance




Less Hot Spot
Shading Effects



Ideal for Residential
Rooftop Application



Linear performance Warranty




Comprehensive Certificates

- ISO9001:2015 QMS
- ISO14001:2015 EMS
- ISO45001:2018 OHSMS
- IEC61215/IEC61730 Standard quality



MECHANICAL CHARACTERISTICS

Solar Cells	Mono
No. of Cells	144 (6x24)
Dimensions	2279 x 1134 x 35mm
Weight	27.5kg
Front Glass	3.2mm coated tempered glass
Frame	Anodized aluminium alloy
Junction Box	Ip68 rated (3 by pass diodes)
	4.0mm ²
Output Cables	300mm (+) / 300mm (-)
	Length can be customized
Connectors	Mc4 compatible
Mechanical load test	5400Pa



ELECTRICAL PARAMETERS


POWER CLASS	LNVU-525M		LNVU-530M		LNVU-535M		LNVU-540M		LNVU-545M	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum power (Pmax)	525W	397W	530W	401W	535W	405W	540W	409W	545W	413W
Open Circuit Voltage (Voc)	49.59V	46.92V	49.74V	47.16V	49.89V	47.40V	50.04V	47.63V	50.18V	47.87V
Short Circuit Current (Isc)	13.55A	10.87A	13.62A	10.91A	13.69A	10.95A	13.76A	10.99A	13.83A	11.03A
Voltage at Maximum power (Vmpp)	41.47V	38.73V	41.63V	38.97V	41.80V	39.21V	41.96V	39.44V	42.12V	39.67V
Current Maximum Power (Impp)	12.66A	10.25A	12.73A	10.29A	12.80A	10.33A	12.87A	10.37A	12.94A	10.41A
MODULE EFFICIENCY (%)	20.31%		20.51%		20.70%		20.89%		21.09%	

STC: Irradiance 1000W/m², cell temperature 25°C, AM1.5G NMOT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s, AM1.5G


PACKING CONFIGURATION

Container	20'GP	40'HQ
Pieces per pallet	31	31
Pallets per container	5	20
Pieces per container	155	620

I-V CURVE



LNVU-545M/I-V



OPERATING CHARACTERISTICS

Operating Module Temperature	-40°C to +85°C
Maximum System Voltage	1500 DC (IEC)
Maximum Series Fuse Rating	25A
Power Tolerance	0/+5W

TEMPERATURE CHARACTERISTICS

Nominal Operating Temperature (NMOT)	45±2°C
Temperature Coefficient of Pmax	-0.36%/°C
Temperature Coefficient of Voc	-0.28%/°C
Temperature Coefficient of Isc	+0.05%/°C

Note: The specifications, data and technical characteristics provided in this data sheet are subject to changes due to continuous R&D, product innovation and improvement. CNB SOLAR reserves the right to modify the information any time without prior notice.